PROSPERO Combined
Word www.f-dgs.com PROSPERO Combined Nitrogen Air Generator - F-DGSi Пересказать Спросить Алису AI

Models	PROSPERO.1		PROSPERO.3		PROSPERO.5
Compressor	0 (Without)	1 (With)	0 (Without)	1 (With)	1 (With)
GENERALS INFORMATIONS					
Max Nitrogen Flow rate	1 L/min		3 L/min		1 L/min
Max Pure Air Flow rate	1.5 L/min		3 L/min		5 L/min
Max N2/Air pressure	6 bar (87 psi)				
Nitrogen purity	> 99.9995% (< 5 ppm O2)				
Pure Air purity	HCs < 0.1 ppm; Air Dew Point < -60°C (-76°F)				
Particles	0.01 µ				
Inlet Air flow required @ 8 bar (116 psi) max	16 L/min	N /A	42 L/min	N /A	N /A
Min Inlet Air quality	ISO8573 – 1:2010 1.4.1	N /A	ISO8573 – 1:2010 1.4.1	N /A	N /A
Touch screen	Touch screen (operating parameters, system status, alarms) with LED indicators(Power on/off; ready or errors)				
Max Relative Humidity	80% RH @ 25°C (77°F)				
Temperature range	From 5 – 25°C (41 – 77°F))				
Max Altitude	3000 Meters				
Noise level @ 1M	25 dB (A)	50 dB (A)	25 dB (A)	52 dB (A)	52 dB (A)
Dimensions (W x H x D)	47.5 x 66.2 x 65 cm (18.7" x 26" x 25,6")		47.5 x 66.2 x 79 cm (18.7" x 26" x 31")		
Weight (kg/lbs)	57 / 125	64 / 141	95 / 209	107 / 236	107 / 2[illegible]
Power consumption	150 VA	350 VA	150 VA	850 VA	850 V
Electrical supply	220 – 240 V ac / 1 ph / 50 – 60 Hz				
	110 – 120 V ac / 1 ph / 50 – 60 Hz				

PROSPERO Combined Nit
Z.PROSPERO Zero Nitr
Word
www.f-dgs.com Z.PROSPERO Zero Nitrogen Air Generator - F-DGSi
Пересказать
Спросить Алису AI

Models	Z.PROSPERO.1		Z.PROSPERO.3		Z.PROSPERO.5
Compressor	0 (Without)	1 (With)	0 (Without)	1 (With)	1 (With)
GENERALS INFORMATIONS					
Max Nitrogen Flow rate	1 L/min		3 L/min		1.5 L/min
Max Pure Air Flow rate	1.5 L/min		3 L/min		5 L/min
Max N2/Air pressure	6 bar (87 psi)				
Nitrogen purity	> 99.9995% (< 5 ppm O2); Total HCs < 0.05 ppm				
Pure Air purity	HCs < 0.1 ppm; Air Dew Point < -60°C (-76°F)				
Particles	0.01 µ				
Inlet Air flow required @ 8 bar (116 psi) max	16 L/min	N /A	42 L/min		N /A
Min Inlet Air quality	ISO8573 – 1:2010 1.4.1	N /A	ISO8573 – 1:2010 1.4.1		N /A
Touch screen	Touch screen (operating parameters, system status, alarms) with LED indicators(Power on/off; ready or errors)				
Max Relative Humidity	80% RH @ 25°C (77°F)				
Temperature range	From 5 – 25°C (41 – 77°F))				
Max Altitude	3000 Meters				
Noise level @ 1M	25 dB (A)	50 dB (A)	25 dB (A)		52 dB (A)
Dimensions (W x H x D)	47.5 x 66.2 x 65 cm (18.7" x 26" x 25,6")		47.5 x 66.2 x 79 cm (18.7" x 26" x 31")		
Weight (kg/lbs)	59 / 130	66 / 145	101 / 223		113 / 249
Power consumption	430 VA	630 VA	430 VA		1130 VA
Electrical supply	220 – 240 V ac / 1 ph / 50 – 60 Hz				
	110 – 120 V ac / 1 ph / 50 – 60 Hz				